

Features

- ± 200 kV/ μ s static CMTI, ± 150 kV/ μ s dynamic CMTI
- 2.2 V input voltage range
- Fixed gain: 1
- Low offset error: 1.5 mV maximum
- Very low gain error: 0.3% maximum
- Very low nonlinearity and drift:
- System-level diagnostic features
- Wide Temperature Range: -40°C to $+125^{\circ}\text{C}$
- WSOP8 package
- Safety-Related Certifications:
 - VDE Certification according to DIN VDE V 0884-17(IEC60747-17)
 - 5000V_{RMS} Isolation Rating per UL 1577
 - CQC Certification per GB 4943.1
 - CAS, TUV and CB certifications

Applications

- Solar Inverter
- Motor Control
- Power Supplies

Description

The TPA8003 is a precision, isolated amplifier with an output separated from the input circuitry by capacitive silicon dioxide insulation barrier. This barrier is certified to provide isolation of up to 5000V_{RMS} according to UL1577.

The common mode transient immunity (CMTI) of the TPA8003 has been significantly enhanced through innovative circuit design and optimized structure.

The input of the TPA8003 is high-impedance which can be connected to high-impedance resistive dividers or any other high-impedance voltage signal source. The excellent performance of the device supports bus voltage in motor control or other applications. The common-mode overvoltage and missing high-side supply voltage detection features of the TPA8003 simplify system-level diagnostics.

The device is available in WSOP8 packages, and is characterized from -40°C to $+125^{\circ}\text{C}$.

Typical Application Circuit

Table of Contents

Features	1
Applications	1
Description	1
Typical Application Circuit.....	1
Revision History	3
Pin Configuration and Functions	4
Specifications	5
Absolute Maximum Ratings ⁽¹⁾	5
ESD, Electrostatic Discharge Protection	5
Recommended Operating Conditions	5
Thermal Information	5
Insulation Specifications.....	6
Safety-Related Certifications	7
Safety Limiting Values	7
Electrical Characteristics	8
Electrical Characteristics	9
Tape and Reel Information.....	10
Package Outline Dimensions	11
WSOP8.....	11
Order Information	12
IMPORTANT NOTICE AND DISCLAIMER.....	13

Revision History

Date	Revision	Notes
2022-11-05	Rev.Pre.0	Pre releasing version
2022-12-01	Rev.Pre.1	Added the VOS spec in 0 to 0.1V input.
2023-03-03	Rev.Pre.2	Updated spec.
2023-08-03	Rev.Pre.3	Updated spec.

Pin Configuration and Functions




Table 6-1. Pin Functions: TPA8003

Pin		Name	I/O	Description
1		VDD1		High-side power supply
2		VIN	Input	analog input
3		SHDN	Input	Shutdown input, active high, with internal pullup resistor. Connect to GND1 to enable the device.
4		GND1		High-side analog ground
5		GND2		Low-side analog ground
6		VOUTN	Output	Negative analog output
7		VOUTP	Output	Positive analog output
8		VDD2		Low-side power supply

Specifications

Absolute Maximum Ratings⁽¹⁾

Parameter		Min	Max	Unit
VDD	Supply voltage, VDD1 to GND1 or VDD2 to GND2	-0.3	7	V
	Analog input voltage at VIN	GND1 – 6	VDD1 + 0.5	V
	Analog input voltage at SHDN	GND1 – 0.5	VDD1 + 0.5	
	Analog output voltage at VOUTP, VOUTN	GND1 – 0.5	VDD2 + 0.5	V
I _{IN}	Input current to any pin except supply pins	-10	10	mA
T _J	Operating virtual junction temperature		150	°C
T _{stg}	Storage temperature	-65	150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

ESD, Electrostatic Discharge Protection

Parameter	Condition	Value	Unit
HBM, per ANSI/ESDA/JEDEC JS-001/ANSI/ESD STM5.5.1 ⁽¹⁾	All Pin	2	kV
CDM, per ANSI/ESDA/JEDEC JS-002 ⁽²⁾	All Pin	1.5	kV

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

Recommended Operating Conditions

Parameter		Min	Typ	Max	Unit
VDD1	High-side supply voltage (VDD1 to GND1)	4.5	5.0	5.5	V
VDD2	Low-side supply voltage (VDD2 to GND2)	3.0	3.3	5.5	V
T _A	Operating ambient temperature	-40	25	125	°C

Thermal Information

Package Type	θ _{JA}	θ _{JC}	Unit
WSOP8	85	43	°C/W

Insulation Specifications

Symbol	Parameter	Conditions	Value			Unit
				WSOP8		
CLR	External clearance	Shortest terminal-to-terminal distance through air		> 8.0		mm
CPG	External creepage	Shortest terminal-to-terminal distance across the package surface		> 8.0		mm
DTI	Distance through the insulation	Minimum internal gap (internal clearance)		> 22		μm
DTC	Distance through the Molding compound	Minimum internal distance across the conductors inside the package		0.8		mm
CTI	Comparative tracking index	DIN EN 60112 (VDE 0303-11); IEC 60112; UL 746A		> 600		V
	Material group	According to IEC 60664-1		I		
	Over-voltage category	For Rated Mains Voltage ≤ 150 V _{RMS}		I-IV		
		For Rated Mains Voltage ≤ 300 V _{RMS}		I-IV		
		For Rated Mains Voltage ≤ 600 V _{RMS}		I-IV		
		For Rated Mains Voltage ≤ 1000 V _{RMS}		I-III		
	Climatic category			40/125/21		
	Pollution degree			2		
DIN V VDE V 0884-17 (1)(2)						
V _{IORM}	Maximum repetitive isolation voltage	AC voltage		1700		V _{PK}
V _{IOWM}	Maximum working isolation voltage	AC voltage; TDDb Test		1200		V _{RMS}
		DC voltage		1700		V _{DC}
V _{IOTM}	Maximum transient isolation voltage	V _{TEST} = V _{IOTM} , t = 60 s (qualification); V _{TEST} = 1.2 × V _{IOTM} , t = 1 s (100% production)		7000		V _{PK}
V _{IOSM}	Maximum surge isolation voltage ⁽³⁾	Test method per IEC 62368-1, 1.2/50 μs waveform, V _{TEST} = 1.3 × V _{IOSM} (qualification)		6500		V _{PK}
q _{pd}	Apparent charge	Method a, After Input/Output safety test subgroup 2/3, V _{ini} = V _{IOTM} , t _{ini} = 60 s; V _{pd(m)} = 1.2 × V _{IORM} , t _m = 10 s		≤ 5		pC
		Method a, After environmental tests subgroup 1, V _{ini} = V _{IOTM} , t _{ini} = 60 s; V _{pd(m)} = 1.6 × V _{IORM} , t _m = 10 s		≤ 5		
		Method b1; At routine test (100% production) and preconditioning (type test), V _{ini} = 1.2 × V _{IOTM} , t _{ini} = 1 s; V _{pd(m)} = 1.875 × V _{IORM} , t _m = 1 s		≤ 5		

2.2-V Input Isolated Amplifier

C _{IO}	Isolation capacitance	V _{IO} = 0.4 × sin (2πft), f = 1 MHz		~0.5		pF
R _{IO}	Isolation resistance	V _{IO} = 500 V, T A= 25°C		> 10 ¹²		Ω
		V _{IO} = 500 V, 100°C ≤ T A≤ 125°C		> 10 ¹¹		Ω
		V _{IO} = 500 V at T S= 150°C		> 10 ⁹		Ω
UL 1577						
V _{ISO}	Withstanding isolation voltage	V _{TEST} = V _{ISO} , t = 60 s(qualification); V _{TEST} = 1.2 × V _{ISO} , t = 1 s (100% production)		5000		V _{RMS}

(1) All pins on each side of the barrier tied together creating a two-terminal device.

(2) This coupler is suitable for safe electrical insulation only within the safety operating ratings. Compliance with the safety ratings shall be ensured by means of suitable protective circuits.

(3) Testing must be carried out in oil.

Safety-Related Certifications

VDE	UL	TUV	CQC	CSA	CB
Certified according to DIN VDE V 0884-17	Certified according to UL 1577 and CSA Component Acceptance Notice 5A	Certified according to EN IEC 62368-1 and EN IEC 61010-1	Certified according to GB 4943.1	Certified CSA C22.2 No. 62368-1 and CAN/CSA-C22.2 No. 60601-1	Certified according to EN IEC 62368-1
Certificate No.	Report Reference	Registration No.	Certificate No.	Master contract:	Ref. Certif. No.

Safety Limiting Values

Parameter	Conditions ⁽¹⁾	Min	Typ	Max	Unit
Safety input, output or supply current	R _{θJA} = 85°C/W, VDD1 = VDD2 = 5.5 V, T _J = 150°C, T _A = 25°C, WSOP8 Package			267	mA
Safety total power	R _{θJA} = 85°C/W, T _J = 150°C, T _A = 25°C, WSOP8 Package			1470	mW
Maximum safety temperature				150	°C

(1) The assumed junction-to-air thermal resistance in the Thermal Information is that of a device installed on a high-K test board for leaded surface-mount packages.

2.2-V Input Isolated Amplifier

Electrical Characteristics

Minimum and maximum specifications apply from $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, $V_{DD1} = 4.5\text{ V}$ to 5.5 V , $V_{DD2} = 3.0\text{ V}$ to 5.5 V , $V_{IN} = 0.1\text{ V}$ to 2 V (unless otherwise noted); typical specifications are at $T_A = 25^{\circ}\text{C}$, $V_{DD1} = 5\text{ V}$, and $V_{DD2} = 3.3\text{ V}$.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
ANALOG INPUT						
VClipping	Input voltage before clipping output	IN to GND1		2.5		V
VFSR	Specified linear full-scale voltage	IN to GND1	0.1		2.2	V
VOS	Input offset voltage	$V_{DD1} = 5\text{ V}$, $V_{DD2} = 5\text{ V}$, In VFSR, $T_A = 25^{\circ}\text{C}$	-1.5	0.4	1.5	mV
		In 0V to 0.1V, $T_A = 25^{\circ}\text{C}$		10		mV
TCV _{OS}	Input offset drift	In VFSR		± 2		$\mu\text{V}/^{\circ}\text{C}$
CIND	Differential input capacitance			7		pF
RIN	Single-ended input resistance	VINN = GND1		1		G Ω
IIB	Input bias current	IN = GND1, $T_A = 25^{\circ}\text{C}$	-15	3	15	nA
ANALOG OUTPUT						
	Nominal gain	VIN at VFSR		1		
E _G	Gain error	$V_{DD1} = 5\text{ V}$, VIN at VFSR, $T_A = 25^{\circ}\text{C}$	-0.3	± 0.05	0.3	%
TCE _G	Gain error drift	$V_{DD1} = 5\text{ V}$, VIN at VFSR	-50	± 15	50	ppm/ $^{\circ}\text{C}$
	Nonlinearity		-0.02	± 0.01	0.02	%
	Nonlinearity drift			1		ppm/ $^{\circ}\text{C}$
THD	Total harmonic distortion	$f_{IN} = 10\text{ kHz}$		-80		dB
	Output noise	VIN = GND1, BW = 100 kHz		300		μVRMS
SNR	Signal-to-noise ratio	$f_{IN} = 1\text{ kHz}$, BW = 10 kHz		80		dB
		$f_{IN} = 10\text{ kHz}$, BW = 100 kHz		70		dB
PSRR	Power-supply rejection ratio	vs VDD1, at dc		-65		dB
		vs VDD1, 100-mV and 10-kHz ripple		-65		dB
		vs VDD2, at dc		-85		dB
		vs VDD2, 100-mV and 10-kHz ripple		-70		dB
CMTI	Common-mode transient immunity	$ \text{GND1} - \text{GND2} = 1\text{ kV}$		150		kV/ μs
VCMout	Common-mode output voltage			1.4		V
	Output short-circuit current			± 15		mA
ROUT	Output resistance	on VOUTP or VOUTN		< 0.2		Ω
BW	Output bandwidth			310		kHz
VCLIPout	Clipping differential output voltage			2.5		V
VFAILSAFE	Failsafe differential output voltage	SHDN = high, or VDD1 undervoltage, or VDD1 missing		-2.56	-2.5	V


(1) Provided by bench test and design simulation

Electrical Characteristics

Minimum and maximum specifications apply from $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, $V_{DD1} = 4.5\text{ V}$ to 5.5 V , $V_{DD2} = 3.0\text{ V}$ to 5.5 V , $V_{IN} = 0.1\text{ V}$ to 2 V (unless otherwise noted); typical specifications are at $T_A = 25^{\circ}\text{C}$, $V_{DD1} = 5\text{ V}$, and $V_{DD2} = 3.3\text{ V}$.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
DIGITAL INPUT						
	Input voltage	SHTDN to GND1	0		VDD1	V
I _{IN}	Input current	SHTDN pin, GND1 ≤ SHTDN ≤ VDD1	−70		1	μA
C _{IN}	Input capacitance	SHTDN pin		5		pF
V _{IH}	High-level input voltage	Shutdown	0.7 × VDD1			V
V _{IL}	Low-level input voltage	Enable			0.3 × VDD1	V
POWER SUPPLY						
	VDD1 undervoltage detection threshold	VDD1 falling		2		V
	VDD2 undervoltage detection threshold	VDD2 falling		2		V
I _{DD1}	High-side supply current	4.5 V ≤ VDD1 ≤ 5.5 V		15		mA
I _{DD2}	Low-side supply current	3.0 V ≤ VDD2 ≤ 3.6 V		8		mA
		4.5 V ≤ VDD2 ≤ 5.5 V		10		mA
SWITCHING CHARACTERISTICS						
t _r	Rise time	See Figure		1		μs
t _f	Fall time	See Figure		1		μs
	V _{IN} to V _{OUT} signal delay (50% – 10%)	See Figure , unfiltered output		0.7		μs
	V _{IN} to V _{OUT} signal delay (50% – 50%)	See Figure , unfiltered output		1.2		μs
	V _{IN} to V _{OUT} signal delay (50% – 90%)	See Figure , unfiltered output		1.8		μs
	Analog settling time	VDD1 step to 5.0 V with VDD2 ≥ 3.0 V, to VOUTP, VOUTN valid, 0.1% settling				μs
	Enable time	Set SHDN high to low				μs
	Shutdown time	Set SHDN low to high				μs

Tape and Reel Information






Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPA8003-SOAR	WSOP8	330	16.4	11.95	6.2	3.0	16.0	16.0	Q1

Package Outline Dimensions

WSOP8

Package Outline Dimensions

SOA(WSOP-8-B)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	2.350	2.650	0.093	0.104
A1	0.100	0.300	0.004	0.012
A2	2.250	2.350	0.089	0.093
b	0.310	0.510	0.012	0.020
c	0.150	0.300	0.006	0.012
D	5.750	5.950	0.226	0.234
E	11.250	11.750	0.443	0.463
E1	7.400	7.600	0.291	0.299
e	1.270 BSC		0.050 BSC	
L	0.500	1.000	0.020	0.039
θ	0	8°	0	8°

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPA8003-SOAR	-40 to 125°C	WSOP8	A8003	MSL3	Tape and Reel, 1000	Green

(1) Can provide sample in 2 months.

(2) Future product, contact 3PEAK factory for more information and sample.

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2023. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.