



900V Super-junction Power MOSFET

Description

900V Super-junction Power MOSFET

Super-junction power MOSFET is a revolutionary technology for high voltage power MOSFETs, designed according to the SJ principle. The deep trench SJ MOSFET provide an extremely low switching, communication and conduction losses device with highest robustness make especially resonant switching applications more reliable, more efficient, lighter and cooler, designed by Wuxi Unigroup Microelectronics Company.


Features

- Very low FOM $R_{DS(on)} \times Q_g$
- 100% avalanche tested
- Easy to use/drive
- RoHS compliant

Applications

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- Low Power Chargers and Adapters

TO-220F




TO-263



TO-220



TO-247



Device Marking and Package Information

Device	Package	Marking
TPA90R350A	TO-220F	90R350A
TPB90R350A	TO-263	90R350A
TPP90R350A	TO-220	90R350A
TPW90R350A	TO-247	90R350A

Key Performance Parameters

Parameter	Value	Unit
$V_{DS} @ T_{j,max}$	950	V
$R_{DS(on),max}$	0.35	Ω
$Q_{g,typ}$	62	nC
I_D	15	A
$I_{D,pulse}$	45	A



Absolute Maximum Ratings $T_C = 25^{\circ}\text{C}$, unless otherwise noted				
Parameter		Symbol	Values	Unit
Continuous Drain Current	$T_C = 25^{\circ}\text{C}$	I_D	15	A
	$T_C = 100^{\circ}\text{C}$		9	
Pulsed Drain Current	(note1)	$I_{D,pulse}$	45	A
Gate-Source Voltage		V_{GSS}	$\pm 30\text{V}$	V
Single Pulse Avalanche Energy	(note2)	E_{AS}	280	mJ
Repetitive Avalanche Energy	(note2)	E_{AR}	0.5	mJ
Avalanche Current		I_{AR}	7.5	A
Power Dissipation For TO-220F		P_D	34	W
Power Dissipation For TO-263, TO-220, TO-247			240	
Continuous Diode Forward Current		I_S	15	A
Diode Pulsed Current	(note1)	$I_{S,pulse}$	45	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	$-55 \sim +150$	$^{\circ}\text{C}$

Thermal Resistance For TO-220F			
Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	R_{thJC}	3.67	$^{\circ}\text{C/W}$
Thermal Resistance, Junction-to-Ambient	R_{thJA}	80	

Thermal Resistance For TO-263, TO-220, TO-247			
Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	R_{thJC}	0.52	$^{\circ}\text{C/W}$
Thermal Resistance, Junction-to-Ambient	R_{thJA}	62	



Electrical Characteristics T _J = 25°C, unless otherwise noted						
Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	900	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 900V, V _{GS} = 0V, T _J = 25°C	--	--	1	μA
		V _{DS} = 900V, V _{GS} = 0V, T _J = 150°C	--	--	100	
Gate-Source Leakage Current	I _{GSS}	V _{GS} = ±30V	--	--	±100	nA
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	2.5	--	4.5	V
Drain-Source On-State-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 7.5A	--	0.31	0.35	Ω
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 50V, f = 1.0MHz	--	2840	--	pF
Output Capacitance	C _{oss}		--	220	--	
Reverse Transfer Capacitance	C _{rss}		--	16	--	
Total Gate Charge	Q _g	V _{DD} = 720V, I _D = 15A, V _{GS} = 10V	--	62	--	nC
Gate-Source Charge	Q _{gs}		--	15	--	
Gate-Drain Charge	Q _{gd}		--	23	--	
Turn-on Delay Time	t _{d(on)}	V _{DD} = 400V, I _D = 15A, R _G = 25Ω	--	49	--	ns
Turn-on Rise Time	t _r		--	42	--	
Turn-off Delay Time	t _{d(off)}		--	166	--	
Turn-off Fall Time	t _f		--	13	--	
Drain-Source Body Diode Characteristics						
Body Diode Forward Voltage	V _{SD}	T _J = 25°C, I _{SD} = 15A, V _{GS} = 0V	--	0.9	1.2	V
Reverse Recovery Time	t _{rr}	V _R = 400V, I _F = I _S , di _F /dt = 100A/μs	--	680	--	ns
Reverse Recovery Charge	Q _{rr}		--	9	--	μC
Peak Reverse Recovery Current	I _{rrm}		--	24	--	A

Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. $I_D = 10A, V_{DD} = 50V, R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$
3. Identical low side and high side switch with identical R_G



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge





Figure 6. Body Diode Forward Voltage





Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. On-Resistance vs. Junction Temperature




Figure 8. Threshold Voltage vs. Junction Temperature




Figure 9. Transient Thermal Impedance For TO-220F




Figure 10. Transient Thermal Impedance For TO-263/TO-220/TO-247




Figure 11. Safe Operation Area For TO-220F




Figure 12. Safe Operation Area For TO-263/TO-220/TO-247






Figure A: Gate Charge Test Circuit and Waveform




Figure B: Resistive Switching Test Circuit and Waveform






Figure C: Unclamped Inductive Switching Test Circuit and Waveform






TO-220F (海天)



项目	规范(mm)	
	MIN	MAX
A	9.70	10.30
B	15.50	16.10
B1	8.99	9.39
C	4.40	4.80
C1	2.15	2.55
D	2.50	2.90
E	0.70	0.90
F	0.40	0.60
G	1.12	1.42
H	3.40	3.80
L	12.6	13.6
N	2.34	2.74
Q	3.15	3.55
ΦP	3.00	3.30




TO-220F (集佳)



SYMBOL	MIN	NOM	MAX
A	4.50	4.70	4.83
A1	2.34	2.54	2.74
A2	0.70 REF		
A3	2.56	2.76	2.93
b	0.70	—	0.90
b1	1.18	—	1.38
b2	—	—	1.47
c	0.45	0.50	0.60
D	15.67	15.87	16.07
D1	15.55	15.75	15.95
D2	9.60	9.80	10.0
E	9.96	10.16	10.36
e	2.54BSC		
H1	6.48	6.68	6.88
L	12.68	12.98	13.28
L1	—	—	3.50
L2	6.50REF		
øP	3.08	3.18	3.28
Q	3.20	—	3.40
θ1	1°	3°	5°




TO-263 (集佳)



SYMBOL	MIN	NOM	MAX
A	4.40	4.50	4.60
A1	0	0.10	0.25
A2	2.20	2.40	2.60
b	0.76	---	0.89
b1	0.75	0.80	0.85
b2	1.23	---	1.37
b3	1.22	1.27	1.32
c	0.47	---	0.60
c1	0.46	0.51	0.56
c2	1.25	1.30	1.35
D	9.10	9.20	9.30
D1	8.00	---	---
E	9.80	9.90	10.00
E1	7.80	---	---
e	2.54 BSC		
H	14.90	15.30	15.70
L	2.00	2.30	2.60
L1	1.17	1.27	1.40
L2	---	---	1.75
L3	0.25BSC		
L4	4.60 REF		
θ	0°	---	8°
θ1	1°	3°	5°




TO-220 (华羿)



Unit:mm				Unit:mm			
Symbol	Min.	Nom	Max.	Symbol	Min.	Nom	Max.
A	4.37	4.57	4.70	E	9.70	10.00	10.30
A1	1.25	1.30	1.40	E3	7.00	-	-
A2	2.20	2.40	2.60	e	2.54 BSC		
b	0.70	0.80	0.95	e1	5.08 BSC		
b2	1.17	1.27	1.47	H1	6.25	6.50	6.85
c	0.45	0.50	0.60	L	12.75	13.50	13.80
D	15.10	15.60	16.10	L1	-	3.10	3.40
D1	8.80	9.10	9.40	ΦP	3.40	3.60	3.80
D2	5.50	-	-	Q	2.60	2.80	3.00



TO-247 (华羿)



SYMBOL	mm		
	MIN	NOM	MAX
A	4.80	5.00	5.20
A1	2.21	2.41	2.59
A2	1.85	2.00	2.15
b	1.11	1.21	1.36
b2	1.91	2.01	2.21
b4	2.91	3.01	3.21
c	0.51	0.61	0.75
D	20.80	21.00	21.30
D1	16.25	16.55	16.85
E	15.50	15.80	16.10
E1	13.00	13.30	13.60
E2	4.80	5.00	5.20
E3	2.30	2.50	2.70
e	5.44BSC		
L	19.82	19.92	20.22
L1	-	-	4.30
ΦP	3.40	3.60	3.80
ΦP1	-	-	7.30
S	6.15BSC		



Disclaimer

All product specifications and data are subject to change without notice.

For documents and material available from this datasheet, Wuxi Unigroup does not warrant or assume any legal liability or responsibility for the accuracy, completeness of any product or technology disclosed hereunder.

No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document or by any conduct of Wuxi Unigroup.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling Wuxi Unigroup products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Wuxi Unigroup for any damages arising or resulting from such use or sale.

Wuxi Unigroup disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Wuxi Unigroup's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

Wuxi Unigroup Microelectronics CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

In the event that any or all Wuxi Unigroup products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

Information (including circuit diagrams and circuit parameters) herein is for example only. It is not guaranteed for volume production. Wuxi Unigroup believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.