

3-Terminal 100mA Positive Voltage Regulator

DESCRIPTION


The TS78L00 Series of positive voltage Regulators are inexpensive, easy-to-use devices suitable for a multitude of applications that require a regulated supply of up to 100mA. Like their higher power TS7800 and TS78M00 Series cousins, these regulators feature internal current limiting and thermal shutdown making them remarkably rugged. No external components are required with the TS78L00 devices in many applications. These devices offer a substantial performance advantage over the traditional zener diode-resistor combination, as output impedance and quiescent current are substantially reduced.

FEATURES

- Output Voltage Range 3.3V, 5V, 9V, 12V, 15V, 24V
- Output current up to 100mA
- No external components required
- Internal thermal overload protection
- Internal short-circuit current limiting
- Output transistor safe-area compensation
- Output voltage offered in 4% tolerance
- RoHS compliant
- Halogen-free according to IEC 61249-2-21

APPLICATION

- Switching power supply
- Home appliance




Notes:

SOT-23: MSL 1 (Moisture Sensitivity Level) per J-STD-020

SOT-89, SOP-8: MSL 3 (Moisture Sensitivity Level) per J-STD-020

TYPICAL APPLICATION CIRCUIT



A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0V above the output voltage even during the low point on the Input ripple voltage.

XX = these two digits of the type number indicate voltage.

* = Cin is required if regulator is located an appreciable distance from power supply filter.

** = Co is not needed for stability; however, it does improve transient response.

ABSOLUTE MAXIMUM RATINGS				
PARAMETER		SYMBOL	LIMIT	UNIT
DC Input Voltage	TS78L03	V_{IN}	30	V
	TS78L05		35	
	TS78L09		35	
	TS78L12		35	
	TS78L15		35	
	TS78L24		40	
Power Dissipation		P_D	Internally Limited	W
Operating Junction Temperature		T_J	+150	°C
Recommended Operating Junction Temperature Range		T_J	-40 ~ +125	°C
Operating Ambient Temperature Range		T_A	-40 ~ +85	°C
Storage Temperature Range		T_{STG}	-65~+150	°C

THERMAL PERFORMANCE					
PARAMETER	SYMBOL	TYPICAL			UNIT
		SOT-23	SOT-89	SOP-8	
Junction to Case Thermal Resistance	$R_{\theta JC}$	120	15	20	°C/W
Junction to Ambient Thermal Resistance	$R_{\theta JA}$	330	55	55	°C/W

Notes: $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins. $R_{\theta JA}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design. $R_{\theta JA}$ shown below for single device operation on FR-4 PCB in still air.

ELECTRICAL SPECIFICATIONS TS78L03

($V_{IN}=8.3V$, $I_{OUT}=40mA$, $0^{\circ}C \leq T_J \leq 125^{\circ}C$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, unless otherwise noted)

PARAMETER	CONDITIONS		SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	T _J =25°C		V _{OUT}	3.173	3.3	3.432	V
	5.8V≤V _{IN} ≤20V, 5mA≤I _{OUT} ≤100mA			3.142	3.3	3.465	V
Line Regulation	T _J =25°C	5.8V≤V _{in} ≤20V I _{OUT} =40mA	REG _{LINE}	--	50	150	mV
Load Regulation	T _J =25°C	5mA≤ I _{OUT} ≤100mA	REG _{LOAD}	--	15	60	mV
		5mA≤I _{OUT} ≤40mA		--	5	30	
Quiescent Current	I _{OUT} =0, T _J =25°C		I _Q	--	3	6	mA
Quiescent Current Change	5.8V≤V _{in} ≤20V		ΔI _Q	--	--	1.5	mA
	5mA≤I _{OUT} ≤40mA			--	--	0.1	
Output Noise Voltage	10Hz≤f≤100kHz, T _J =25°C		V _N	--	40	--	μV
Ripple Rejection Ratio	F=120Hz, 5.8V≤V _{in} ≤20V		RR	41	49	--	dB
Voltage Drop	I _{OUT} =100mA, T _J =25°C		V _{DROP}	--	2	--	V
Peak Output Current	T _J =25°C		I _{o peak}	--	0.15	--	A
Temperature Coefficient of Output Voltage	I _{OUT} =5mA, 0°C≤T _J ≤150°C		ΔV _{OUT} / ΔT _J	--	-0.2	--	mV/ °C

ELECTRICAL SPECIFICATIONS TS78L05

($V_{IN}=10V$, $I_{OUT}=40mA$, $0^{\circ}C \leq T_J \leq 125^{\circ}C$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, unless otherwise noted)

PARAMETER	CONDITIONS		SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	T _J =25°C		V _{OUT}	4.80	5	5.20	V
	7.5V≤V _{in} ≤20V, 5mA≤I _{OUT} ≤100mA			4.75	5	5.25	V
Line Regulation	T _J =25°C	7.5V≤V _{in} ≤20V I _{OUT} =100mA	REG _{LINE}	50	150	150	mV
Load Regulation	T _J =25°C	5mA≤I _{OUT} ≤100mA	REG _{LOAD}	20	60	60	mV
		5mA≤I _{OUT} ≤40mA		10	30	30	
Quiescent Current	I _{OUT} =0, T _J =25°C		I _Q	--	3	6	mA
Quiescent Current Change	7.5V≤V _{in} ≤20V		ΔI _Q	--	--	1.5	mA
	5mA≤I _{OUT} ≤40mA			--	--	0.1	
Output Noise Voltage	10Hz≤f≤100kHz, T _J =25°C		V _N	--	40	--	μV
Ripple Rejection Ratio	F=120Hz, 7.5V≤V _{in} ≤20V		RR	41	49	--	dB
Voltage Drop	I _{OUT} =100mA, T _J =25°C		V _{DROP}	--	1.7	--	V
Peak Output Current	T _J =25°C		I _{o peak}	--	0.15	--	A
Temperature Coefficient of Output Voltage	I _{OUT} =5mA, 0°C≤T _J ≤150°C		ΔV _{OUT} / ΔT _J	--	-0.65	--	mV/ °C

Note:

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

ELECTRICAL SPECIFICATIONS TS78L09

($V_{IN}=15V$, $I_{OUT}=40mA$, $0^{\circ}C \leq T_J \leq 125^{\circ}C$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, unless otherwise noted)

PARAMETER	CONDITIONS		SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	T _J =25°C		V _{OUT}	8.65	9	9.36	V
	11.5V≤V _{in} ≤23V, 5mA≤I _{OUT} ≤100mA			8.57	9	9.45	V
Line Regulation	T _J =25°C	11.5V≤V _{in} ≤23V I _{OUT} =40mA	REG _{LINE}	--	90	180	mV
Load Regulation	T _J =25°C	5mA≤I _{OUT} ≤100mA	REG _{LOAD}	--	30	90	mV
		5mA≤I _{OUT} ≤40mA		--	15	45	
Quiescent Current	I _{OUT} =0, T _J =25°C		I _Q	--	3	6	mA
Quiescent Current Change	11.5V≤V _{in} ≤23V		ΔI _Q	--	--	1.5	mA
	5mA≤I _{OUT} ≤40mA			--	--	0.1	
Output Noise Voltage	10Hz≤f≤100kHz, T _J =25°C		V _N	--	60	--	μV
Ripple Rejection Ratio	F=120Hz, 11.5V≤V _{in} ≤23V		RR	37	57	--	dB
Voltage Drop	I _{OUT} =100mA, T _J =25°C		V _{DROP}	--	1.7	--	V
Peak Output Current	T _J =25°C		I _{o peak}	--	0.15	--	A
Temperature Coefficient of Output Voltage	I _{OUT} =5mA, 0°C≤T _J ≤150°C		ΔV _{OUT} / ΔT _J	--	-0.9	--	mV/ °C

ELECTRICAL SPECIFICATIONS TS78L12

($V_{IN}=19V$, $I_{OUT}=40mA$, $0^{\circ}C \leq T_J \leq 125^{\circ}C$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, unless otherwise noted)

PARAMETER	CONDITIONS		SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	T _J =25°C		V _{OUT}	11.53	12	12.48	V
	14.5V≤V _{in} ≤27V, 5mA≤I _{OUT} ≤100mA			11.42	12	12.60	V
Line Regulation	T _J =25°C	14.5V≤V _{in} ≤27V I _{OUT} =40mA	REG _{LINE}	--	120	240	mV
Load Regulation	T _J =25°C	5mA≤I _{OUT} ≤100mA	REG _{LOAD}	--	40	120	mV
		5mA≤I _{OUT} ≤40mA		--	20	60	
Quiescent Current	I _{OUT} =0, T _J =25°C		I _Q	--	3	6.5	mA
Quiescent Current Change	14.5V≤V _{in} ≤27V		ΔI _Q	--	--	1.5	mA
	5mA≤I _{OUT} ≤40mA			--	--	0.1	
Output Noise Voltage	10Hz≤f≤100kHz, T _J =25°C		V _N	--	80	--	μV
Ripple Rejection Ratio	F=120Hz, 14.5V≤V _{in} ≤27V		RR	37	42	--	dB
Voltage Drop	I _{OUT} =100mA, T _J =25°C		V _{DROP}	--	1.7	--	V
Peak Output Current	T _J =25°C		I _{o peak}	--	0.15	--	A
Temperature Coefficient of Output Voltage	I _{OUT} =5mA, 0°C≤T _J ≤150°C		ΔV _{OUT} / ΔT _J	--	-1.0	--	mV/ °C

Note:

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

ELECTRICAL SPECIFICATIONS TS78L15

($V_{IN}=23V$, $I_{OUT}=40mA$, $0^{\circ}C \leq T_J \leq 125^{\circ}C$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, unless otherwise noted)

PARAMETER	CONDITIONS		SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	T _J =25°C		V _{OUT}	14.42	15	15.60	V
	17.5V≤V _{IN} ≤30V, 5mA≤I _{OUT} ≤100mA			14.28	15	15.75	V
Line Regulation	T _J =25°C	17.5V≤V _{IN} ≤30V I _{OUT} =40mA	REG _{LINE}	--	150	300	mV
Load Regulation	T _J =25°C	5mA≤I _{OUT} ≤100mA	REG _{LOAD}	--	50	150	mV
		5mA≤I _{OUT} ≤40mA		--	25	75	
Quiescent Current	I _{OUT} =0, T _J =25°C		I _Q	--	3	6.6	mA
Quiescent Current Change	17.5V≤V _{IN} ≤30V		ΔI _Q	--	--	1.5	mA
	5mA≤I _{OUT} ≤40mA			--	--	0.1	
Output Noise Voltage	10Hz≤f≤100kHz, T _J =25°C		V _N	--	90	--	μV
Ripple Rejection Ratio	F=120Hz, 17.5V≤V _{IN} ≤30V		RR	34	39	--	dB
Voltage Drop	I _{OUT} =100mA, T _J =25°C		V _{DROP}	--	1.7	--	V
Peak Output Current	T _J =25°C		I _{o peak}	--	0.15	--	A
Temperature Coefficient of Output Voltage	I _{OUT} =5mA, 0°C≤T _J ≤150°C		ΔV _{OUT} / ΔT _J	--	-1.3	--	mV/ °C

ELECTRICAL SPECIFICATIONS TS78L24

($V_{IN}=33V$, $I_{OUT}=40mA$, $0^{\circ}C \leq T_J \leq 125^{\circ}C$, $C_{IN}=0.33\mu F$, $C_{OUT}=0.1\mu F$, unless otherwise noted)

PARAMETER	CONDITIONS		SYMBOL	MIN	TYP	MAX	UNIT
Output voltage	T _J =25°C		V _{OUT}	23.07	24	24.96	V
	27V≤V _{in} ≤38V, 5mA≤I _{OUT} ≤100mA			22.85	24	25.20	V
Line Regulation	T _J =25°C	27≤V _{in} ≤38V I _{OUT} =40mA	REG _{LINE}	--	200	400	mV
Load Regulation	T _J =25°C	5mA≤I _{OUT} ≤100mA	REG _{LOAD}	--	80	240	mV
		5mA≤I _{OUT} ≤40mA		--	40	120	
Quiescent Current	I _{OUT} =0, T _J =25°C		I _Q	--	4	7	mA
Quiescent Current Change	27V≤V _{in} ≤38V		ΔI _Q	--	--	1.5	mA
	5mA≤I _{OUT} ≤40mA			--	--	0.1	
Output Noise Voltage	10Hz≤f≤100kHz, T _J =25°C		V _N	--	200	--	μV
Ripple Rejection Ratio	F=120Hz, 27V≤V _{in} ≤38V		RR	31	45	--	dB
Voltage Drop	I _{OUT} =100mA, T _J =25°C		V _{DROP}	--	1.7	--	V
Peak Output Current	T _J =25°C		I _{o peak}	--	0.15	--	A
Temperature Coefficient of Output Voltage	I _{OUT} =5mA, 0°C≤T _J ≤150°C		ΔV _{OUT} / ΔT _J	--	-2.0	--	mV/ °C

Note:

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

ORDERING INFORMATION

OUTPUT VOLTAGE	PART NO.	PACKAGE	PACKING
3.3V	TS78L03ACY RMG	SOT-89	1,000pcs / 7" Reel
	TS78L03CX RFG	SOT-23	3,000pcs / 7" Reel
	TS78L03CS RLG	SOP-8	2,500pcs / 13" Reel
5V	TS78L05ACY RMG	SOT-89	1,000pcs / 7" Reel
	TS78L05CX RFG	SOT-23	3,000pcs / 7" Reel
	TS78L05CS RLG	SOP-8	2,500pcs / 13" Reel
9V	TS78L09ACY RMG	SOT-89	1,000pcs / 7" Reel
	TS78L09CX RFG	SOT-23	3,000pcs / 7" Reel
	TS78L09CS RLG	SOP-8	2,500pcs / 13" Reel
12V	TS78L12ACY RMG	SOT-89	1,000pcs / 7" Reel
	TS78L12CS RLG	SOP-8	2,500pcs / 13" Reel
15V	TS78L15ACY RMG	SOT-89	1,000pcs / 7" Reel
	TS78L15CS RLG	SOP-8	2,500pcs / 13" Reel
24V	TS78L24CS RLG	SOP-8	2,500pcs / 13" Reel


APPLICATION INFORMATION

Design Considerations

The TS78L00 Series of fixed voltage regulators are designed with Thermal Overload Protection that shuts down the circuit when subjected to an excessive power overload condition. Internal Short Circuit protection limits the maximum current the circuit will pass.

In many low current applications, compensation capacitors are not required. However, it is recommended that the regulator input be bypassed with a capacitor if the regulator is connected to the power supply filter with long wire lengths, or if the output load capacitance is large. The input bypass capacitor should be selected to provide good high-frequency characteristics to insure stable operation under all load conditions. A 0.33μF or larger tantalum, mylar, or other capacitor having low internal impedance at high frequencies should be chosen. The bypass capacitor should be mounted with the shortest possible leads directly across the regulators input terminals. Good construction techniques should be used to minimize ground loops and lead resistance drops since the regulator has no external sense lead. Bypassing the output is also recommended.

FIGURE 1 – Current Regulator



The TS78L00 regulators can also be used as a current source when connected as above. In order to minimize dissipation the TS78L05 is chosen in this application. Resistor R determines the current as follows:

$$I_O = \frac{5.0V}{R} + I_B$$

$I_B = 3.8\text{mA}$ over lined and load changes

For example, a 100mA current source would require R to be a 50Ω, 1/2W resistor and the output voltage compliance would be the input voltage less 7V.

FIGURE 2 – ±15V Tracking Voltage Regulator





FIGURE 3 – ±15V Tracking Voltage Regulator



ELECTRICAL CHARACTERISTICS CURVE




Fig 1. Output Voltage vs. Ambient Temperature




Fig 2. Output Voltage vs. Output Current




Fig 3. Quiescent Current vs. Input Current




Fig 4. Quiescent Current vs. Temperature










Fig 5. Output Voltage vs. $V_{IN} - V_{OUT}$ Diff.

PACKAGE OUTLINE DIMENSIONS

SOT-89



XX = Output Voltage

03 =3.3V **05** =5.0V **09** =9V **12** =12V **15** =15V

Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr

S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec







L = Lot Code

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEDEC TO-243, ISSUE C, VARIATION AA.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
5. DWG NO REF: HQ2SD07-024 REV A.

PACKAGE OUTLINE DIMENSIONS

SOT-23



XX = Output Voltage

L3 =3.3V **L5** =5.0V **L9** =9V

Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr

S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec


L = Lot Code

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEDEC TO-236, ISSUE H, VARIATION AA.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
5. DWG NO REF: HQ2SD07-025 REV A.

PACKAGE OUTLINE DIMENSIONS

SOP-8



XX = Output Voltage

03 =3.3V **05** =5.0V **09** =9V **12** =12V **15** =15V
24 =24V

Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr
S =May **T** =Jun **U** =Jul **V** =Aug
W =Sep **X** =Oct **Y** =Nov **Z** =Dec

L = Lot Code

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEDEC MS-012, ISSUE G, VARIATION AA.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
5. DWG NO REF: HQ2SD07-SOP8STD-028 REV A.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.