

S5 Module with low loss IGBT and Fast recovery diode.


Feature

- Low $V_{CE(sat)}$ Trench IGBT technology
- 10 μ s short circuit capability
- Maximum junction temperature 175 $^{\circ}$ C

Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

Appearance



Maximum Ratings of Inverter IGBT ($T_{vj}=25^{\circ}$ C unless otherwise noted)

Items	Symbol	Conditions	Maximum Rating	Units
Collector-emitter voltage	V_{CES}		1200	V
Gate-emitter voltage	V_{GES}		± 20	V
Collector current	I_C	$T_{vj}=25^{\circ}$ C	80	A
		$T_{vj}=100^{\circ}$ C	40	A
Pulsed collector current	I_{CM}	$t_p=1ms$	80	A
Short circuit current	I_{sc}	$V_{GE} \leq 15V, V_{CC}=600V, t_p=10\mu s$ $V_{CEmax}=V_{CES}-L_{sCE} \cdot di/dt$	160	A
Maximum power dissipation	P_D	$T_c=25^{\circ}$ C, $T_{vj}=150^{\circ}$ C	210	W

Electrical Characteristics of Inverter IGBT ($T_{vj}=25^{\circ}$ C unless otherwise noted)

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Collector-emitter breakdown voltage	V_{CES}	$V_{GE}=0V, I_C=1mA$	1200			V
Collector -emitter leakage current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V$			2.0	mA
Gate leakage current, forward	I_{GES}	$V_{GE}=20V, V_{CE}=0V$			400	nA
		$V_{GE}=-20V, V_{CE}=0V$			-400	nA
Gate threshold voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=24mA$	5.0	5.8	7.0	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=40A, T_{vj}=25^{\circ}$ C		1.9	2.2	V
		$V_{GE}=15V, I_C=40A, T_{vj}=125^{\circ}$ C		2.1		V
Integrated gate resistor	R_{Gint}	$f=1MHz, V_{pp}=1V$		6.0		Ω
Input capacitance	C_{ies}	$V_{CE}=25V$		2.50		nF
Output capacitance	C_{oes}	$V_{GE}=0V$		0.20		nF
Reverse transfer capacitance	C_{res}	$f=1MHz$		0.09		nF
Total gate charge	Q_g	$V_{GE}=\pm 15V$		0.33		uC
Turn-on delay time	$t_{d(on)}$	$V_{CC}=600V$		90		ns
Rise time	t_r	$V_{GE}=\pm 15V$		30		ns
Turn-off delay time	$t_{d(off)}$	$I_C=40A$		420		ns
Fall time	t_f	$R_G=22\Omega$		70		ns
Turn-on energy loss per pulse	E_{on}	Inductive Load $T_{vj}=25^{\circ}$ C		4.10		mJ
Turn-off energy loss per pulse	E_{off}			3.60		mJ
Turn-on delay time	$t_{d(on)}$	$V_{CC}=600V$		90		ns
Rise time	t_r	$V_{GE}=\pm 15V$		50		ns
Turn-off delay time	$t_{d(off)}$	$I_C=40A$		520		ns
Fall time	t_f	$R_G=22\Omega$		90		ns
Turn-on energy loss per pulse	E_{on}	Inductive Load $T_{vj}=25^{\circ}$ C		5.80		mJ
Turn-off energy loss per pulse	E_{off}			4.20		mJ
Temperature under switching conditions	$T_{vj op}$		-55		150	$^{\circ}$ C

Maximum Ratings of Inverter Diode

Items	Symbol	Conditions	Maximum Rating	Units
Repetitive peak reverse voltage	V_{RRM}	$T_{vj}=25^{\circ}C$	1200	V
Diode continuous forward current	I_F	$T_{vj}=25^{\circ}C$	80	A
		$T_{vj}=100^{\circ}C$	40	A
Diode maximum forward current	I_{FM}	$t_p=1ms, T_{vj}=25^{\circ}C$	80	A

Electrical s Characteristics of Inverter Diode ($T_{vj}=25^{\circ}C$ unless otherwise noted)

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Diode forward voltage	V_F	$I_F=40A, T_{vj}=25^{\circ}C$		1.80		V
		$I_F=40A, T_{vj}=125^{\circ}C$		1.80		V
Diode peak reverse recovery current	I_{rr}	$V_{CE}=600V, I_F=40A$		45		A
Diode reverse recovery charge	Q_{rr}	$dI_F/dt=900A/\mu s$		4.40		μC
Reverse recovery energy	E_{rec}	$T_{vj}=25^{\circ}C$		1.55		mJ
Diode peak reverse recovery current	I_{rr}	$V_{CE}=600V, I_F=40A$		46		A
Diode reverse recovery charge	Q_{rr}	$dI_F/dt=900A/\mu s$		8.40		nC
Reverse recovery energy	E_{rec}	$T_{vj}=25^{\circ}C$		3.10		mJ

Maximum Ratings of Rectifier Diode

Items	Symbol	Conditions	Maximum Rating	Units
Repetitive peak reverse voltage	V_{RRM}	$T_C=25^{\circ}C$	1600	V
Maximum RMS forward current per chip	I_{FRMSM}	$T_C=80^{\circ}C$	50	A
Maximum RMS current at rectifier output	I_{RMSM}	$T_C=80^{\circ}C$	50	A
Surge forward current	I_{FSM}	$T_{vj}=80^{\circ}C, t_p=10ms$	400	A
I^2t - value	I^2t	$t_p = 10 ms, T_{vj} = 25^{\circ}C$	900	A^2s

Electrical s Characteristics of Rectifier Diode ($T_{vj}=25^{\circ}C$ unless otherwise noted)

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Forward voltage	V_F	$I_F=25A, T_{vj}=25^{\circ}C$		1.00		V
Reverse current	I_r	$V_{CE}=1600V$		2.00		mA
Temperature under switching conditions	$T_{vj op}$		-40		150	$^{\circ}C$

Maximum Ratings of Inverter Brake IGBT ($T_{vj}=25^{\circ}C$ unless otherwise noted)

Items	Symbol	Conditions	Maximum Rating	Units
Collector-emitter voltage	V_{CES}		1200	V
Gate-emitter voltage	V_{GES}		± 20	V
Collector current	I_C	$T_{vj}=25^{\circ}C$	50	A
		$T_{vj}=100^{\circ}C$	25	A
Pulsed collector current	I_{CM}	$t_p=1ms$	50	A
Short circuit current	I_{sc}	$V_{GE} \leq 15V, V_{CC}=600V, t_p=10\mu s$ $V_{CEmax}=V_{CES}-L_{sCE} \cdot di/dt$	90	A
Maximum power dissipation	P_D	$T_c=25^{\circ}C, T_{vj}=150^{\circ}C$	160	W

Electrical Characteristics of Brake IGBT ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Collector-emitter breakdown voltage	V_{CES}	$V_{GE}=0V, I_C=1mA$	1200			V
Collector -emitter leakage current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V$			1.0	mA
Gate leakage current, forward	I_{GES}	$V_{GE}=20V, V_{CE}=0V$			100	nA
		$V_{GE}=-20V, V_{CE}=0V$			-100	nA
Gate threshold voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=24mA$	5.0	5.8	7.0	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=25A, T_{vj}=25^{\circ}\text{C}$		1.9	2.2	V
		$V_{GE}=15V, I_C=25A, T_{vj}=125^{\circ}\text{C}$		2.1		V
Integrated gate resistor	R_{Gint}	$f=1M; V_{pp}=1V$		0.0		Ω
Input capacitance	C_{ies}	$V_{CE}=25V$		1.40		nF
Output capacitance	C_{oes}	$V_{GE}=0V$		0.10		nF
Reverse transfer capacitance	C_{res}	$f=1MHz$		0.05		nF
Total gate charge	Q_g	$V_{CC}=600V, V_{GE}=15V, I_C=25A$		0.20		μC
Turn-on delay time	$t_{d(on)}$	$V_{CC}=600V$		160		ns
Rise time	t_r	$V_{GE}=\pm 15V$		30		ns
Turn-off delay time	$t_{d(off)}$	$I_C=25A$		330		ns
Fall time	t_f	$R_G=20\Omega$		80		ns
Turn-on energy loss per pulse	E_{on}	Inductive Load $T_{vj}=25^{\circ}\text{C}$		1.85		mJ
Turn-off energy loss per pulse	E_{off}			1.43		mJ
Turn-on delay time	$t_{d(on)}$	$V_{CC}=600V$		170		ns
Rise time	t_r	$V_{GE}=\pm 15V$		40		ns
Turn-off delay time	$t_{d(off)}$	$I_C=25A$		430		ns
Fall time	t_f	$R_G=20\Omega$		150		ns
Turn-on energy loss per pulse	E_{on}	Inductive Load $T_{vj}=25^{\circ}\text{C}$		2.50		mJ
Turn-off energy loss per pulse	E_{off}			2.10		mJ
Temperature under switching conditions	$T_{vj op}$		-55		150	$^{\circ}\text{C}$

Maximum Ratings of Brake Diode

Items	Symbol	Conditions	Maximum Rating	Units
Repetitive peak reverse voltage	V_{RRM}	$T_{vj}=25^{\circ}\text{C}$	1200	V
Diode continuous forward current	I_F	$T_{vj}=25^{\circ}\text{C}$	30	A
		$T_{vj}=100^{\circ}\text{C}$	15	A
Diode maximum forward current	I_{FM}	$t_p=1ms, T_{vj}=25^{\circ}\text{C}$	30	A

Electrical Characteristics of Brake Diode ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Diode forward voltage	V_F	$I_F=15A, T_{vj}=25^{\circ}\text{C}$		1.80		V
		$I_F=15A, T_{vj}=125^{\circ}\text{C}$		1.80		V
Diode peak reverse recovery current	I_{rr}	$V_{CE}=600V, I_F=25A$		20		A
Diode reverse recovery charge	Q_{rr}	$dI_F/dt=900A/\mu\text{s}$		1.50		μC
Reverse recovery energy	E_{rec}	$T_{vj}=25^{\circ}\text{C}$		0.40		mJ
Diode peak reverse recovery current	I_{rr}	$V_{CE}=600V, I_F=25A$		30		A
Diode reverse recovery charge	Q_{rr}	$dI_F/dt=900A/\mu\text{s}$		2.70		nC
Reverse recovery energy	E_{rec}	$T_{vj}=25^{\circ}\text{C}$		0.90		mJ

Characteristics of NTC ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Rated resistance	R_{25}			5.00		
Deviation of R100	$\Delta R/R$	$T_C = 100^{\circ}\text{C}$, $R_{100} = 493 \text{ W}$	-5		5	%
Power dissipation	P_{25}				20.0	mW
B-value	$B_{25/50}$	$R_2=R_{25} \exp [B_{25/50}(1/T_2-1/(298,15 \text{ K}))]$		3375		K
B-value	$B_{25/80}$	$R_2=R_{25} \exp [B_{25/80}(1/T_2-1/(298,15 \text{ K}))]$		3411		K
B-value	$B_{25/100}$	$R_2=R_{25} \exp [B_{25/100}(1/T_2-1/(298,15 \text{ K}))]$		3433		K


Thermal Characteristics

Items	Symbol	Min.	typ.	Max.	Units
Thermal resistance, junction to case for Inverter IGBT	$R_{th j-c}$			0.60	$^{\circ}\text{C/W}$
Thermal resistance, junction to case for Inverter Diode	$R_{th j-c}$			0.95	$^{\circ}\text{C/W}$
Thermal resistance, junction to case for Rectifier Diode	$R_{th j-c}$			1.00	$^{\circ}\text{C/W}$
Thermal resistance, junction to case for Brake IGBT	$R_{th j-c}$			1.20	$^{\circ}\text{C/W}$
Thermal resistance, junction to case for Brake Diode	$R_{th j-c}$			2.30	$^{\circ}\text{C/W}$
Thermal resistance, case to sink	$R_{th C-S}$		0.03		$^{\circ}\text{C/W}$

Module Characteristics

Items	Symbol	Conditions	Min.	typ.	Max.	Units
Material of module baseplate				Cu		
Internal isolation		terminal to terminal		Al_2O_3		
Isolation test voltage	V_{isol}	RMS, $f = 50 \text{ Hz}$, $t = 1 \text{ min.}$	2.5			kV
Stray inductance module	L_{sCE}			30		nH
Mounting torque for modul mounting	M	Screw M5	3.0		5.0	Nm
Storage temperature range	T_{STG}		-55		150	$^{\circ}\text{C}$
Weight of Module	W_t			180		g

Internal Circuit:



Representative Characteristics

Fig 1. Output characteristic IGBT

$$I_C = f(V_{CE}), V_{GE} = 15V$$




Fig 2. Output characteristic IGBT

$$I_C = f(V_{CE})$$

$$T_{vj} = 125^\circ C$$




Fig 3. Transfer characteristic IGBT

$$I_C = f(V_{GE})$$

$$V_{CE} = 20V$$




Fig 4. Switching losses IGBT

$$E_{on} = f(I_C), E_{off} = f(I_C)$$

$$V_{GE} = \pm 15V, R_G = 22\Omega, V_{CE} = 600V$$




Fig 5. Switching losses IGBT

$$E_{on}=f(R_G), E_{off}=f(R_G),$$

$$V_{GE}=\pm 15V, I_C=40A, V_{CE}=600V$$




Fig 6. Transient thermal impedance IGBT

$$Z_{thjc}=f(t)$$




Fig 7. Reverse bias safe operating area IGBT,

$$I_C=f(V_{CE})$$

$$V_{GE}=\pm 15V, R_{Goff}=22\Omega, T_{vj}=125^\circ C$$




Fig 8. Forward characteristic of Diode

$$I_F=f(V_F)$$




Fig 9. Switching losses Diode

$$E_{rec}=f(I_F)$$

$$R_G=22\Omega, V_{CE}=600V$$




Fig 10. Switching losses Diode

$$E_{rec}=f(R_G)$$

$$I_F=40A, V_{CE}=600V$$




Fig 11. transient thermal impedance Inverter Diode
 $Z_{thjc}=f(t)$






Fig12. Forward characteristic of Rectifier Diode
 $I_F=f(V_F)$



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff who will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

Information in this document is believed to be accurate and reliable. However, TaiXin does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

If you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the Salesman, which is responsible for you. For those that are specifically interested we may provide application notes.

Right to make changes TaiXin reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice.