

Voltage Controlled Crystal Oscillator

- Ultra miniature ceramic SMD package
- 2.0MHz to 47.0MHz
- HCMOS output
- Broad range of Pullability specifications
- Tight symmetry available




VO420

Specifications:

Frequency Range:	2.0 MHz ~ 47.0 MHz	
Operating Temperature:	-10°C ~ +60°C	- B
	-20°C ~ +70°C	- C
	-30°C ~ +75°C	- D
	-40°C ~ +85°C	- U
Storage Temperature:	-40°C ~ +125°C	
Stability Vs. Temperature:	± 25ppm max	- 25
	± 30ppm max	- 30
	± 50ppm max	- 50
Vs. Input Voltage:	± 5ppm ± 5%	
Aging:	± 5ppm max first year	
Pulling Range:	± 100 ppm	- Standard
Control Voltage:	0.5V to 4.5V (V _{DD} =5V)	
	0.3V to 3.0V (V _{DD} =3.3V)	
Output Waveform	HCMOS/15pF/50±5%	- J
	HCMOS/50pF/50±5%	- F
Rise/Fall Time	8ns max (2MHz ~ 20MHz)	
	5ns max (20MHz ~ 47MHz)	
Current Consumption:	40mA max (V _{DD} =5.0V)	
	20mA max (V _{DD} =3.3V)	
Supply Voltage:	3.3V ± 10%	- Standard
	5.0V ± 10%	- P

www.DataSheet4U.com

VO-C



Pin	Configurations
#1	Vcon
#2	Ground
#3	Output
#4	Supply V _{DD}

All dimensions are in mm

Note:

1. Other frequencies, stabilities, and operating temperature ranges available. Consult VTC Support for specific requirements.
2. Not all combinations of the above, stabilities, and temperature ranges are available. Consult VTC Support if your requirement is not standard.
3. All specifications subject to change without notice.

Ordering Information

Product name + Temperature Code + Stability + Output Code + Pulling Range + V_{DD} Code + Frequency.

i.e. VO420C25FP - 27.0MHz