


P-Channel Enhancement Mode Power MOSFET

Pb Lead(Pb)-Free




DRAIN CURRENT

-3.7 AMPERES

DRAIN SOURCE VOLTAGE

-30 VOLTAGE



SOT-23

Features:

- *Super High Dense Cell Design For Low $R_{DS(ON)}$
 $R_{DS(ON)} < 75m\Omega @ V_{GS} = -10V$
- *Rugged and Reliable
- *Simple Drive Requirement
- *SOT-23 Package

Maximum Ratings($T_A = 25^\circ C$ Unless Otherwise Specified)

Rating	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current ³ , ($T_A = 25^\circ C$) , ($T_A = 70^\circ C$)	I_D	-3.7	A
		-3.0	
Pulsed Drain Current ^{1,2}	I_{DM}	-12	
Total Power Dissipation($T_A = 25^\circ C$)	P_D	1.38	W
Maximum Thermal Resistance Junction-ambient ³	$R_{\theta JA}$	90	$^\circ C/W$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^\circ C$

Device Marking

WTC2309=2309

Electrical Characteristics ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

Static

Drain-Source Breakdown Voltage $V_{GS}=0, I_D=-250\mu\text{A}$	$V_{(BR)DSS}$	-30	-	-	V
Gate-Source Threshold Voltage $V_{DS}=V_{GS}, I_D=-250\mu\text{A}$	$V_{GS(Th)}$	-1.0	-	-3.0	
Gate-Source Leakage Current $V_{GS} = \pm 20\text{V}$	I_{GSS}	-	-	± 100	nA
Drain- Source Leakage Current($T_j=25^\circ\text{C}$) $V_{DS}=-30\text{V}, V_{GS}=0$	I_{DSS}	-	-	-1	μA
Drain- Source Leakage Current($T_j=55^\circ\text{C}$) $V_{DS}=-24\text{V}, V_{GS}=0$		-	-	-25	
Drain-Source On-Resistance ² $V_{GS}=-10\text{V}, I_D=-3.0\text{A}$ $V_{GS}=-4.5\text{V}, I_D=-2.6\text{A}$	$R_{DS(on)}$	- -	- -	75 120	$\text{m}\Omega$
Forward Transconductance $V_{DS}=-10\text{V}, I_D=-3\text{A}$	g_{fs}	-	5.0	-	S

Dynamic

Input Capacitance $V_{GS}=0\text{V}, V_{DS}=-25\text{V}, f=1.0\text{MHz}$	C_{iss}	-	412	660	pF
Output Capacitance $V_{GS}=0\text{V}, V_{DS}=-25\text{V}, f=1.0\text{MHz}$	C_{oss}	-	91	-	
Reverse Transfer Capacitance $V_{GS}=0\text{V}, V_{DS}=-25\text{V}, f=1.0\text{MHz}$	C_{rss}	-	62	-	

Switching

Turn-on Delay Time ² $V_{DS}=-15V, V_{GS}=-10V, I_D=-1A, R_D=15\Omega, R_G=3.3\Omega$	$t_{d(on)}$	-	8	-	ns
Rise Time $V_{DS}=-15V, V_{GS}=-10V, I_D=-1A, R_D=15\Omega, R_G=3.3\Omega$	t_r	-	5	-	
Turn-off Delay Time $V_{DS}=-15V, V_{GS}=-10V, I_D=-1A, R_D=15\Omega, R_G=3.3\Omega$	$t_{d(off)}$	-	20	-	
Fall Time $V_{DS}=-15V, V_{GS}=-10V, I_D=-1A, R_D=15\Omega, R_G=3.3\Omega$	t_f	-	7	-	
Total Gate Charge ² $V_{DS}=-24V, V_{GS}=-4.5V, I_D=-3A$	Q_g	-	5	8	nC
Gate-Source Charge $V_{DS}=-24V, V_{GS}=-4.5V, I_D=-3A$	Q_{gs}	-	1	-	
Gate-Drain Charge $V_{DS}=-24V, V_{GS}=-4.5V, I_D=-3A$	Q_{gd}	-	3	-	







Source-Drain Diode Characteristics







Forward On Voltage ² $V_{GS}=0V, I_S=-1.2A$	V_{SD}	-	-	-1.2	V
Reverse Recovery Time ² $V_{GS}=0V, I_S=-3.0A, di/dt=100A/\mu s$	T_{rr}	-	20	-	ns
Reverse Recovery Charge $V_{GS}=0V, I_S=-3.0A, di/dt=100A/\mu s$	Q_{rr}	-	15	-	nC

Note: 1. Pulse width limited by Max, junction temperature.


2. pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.

3. Surface mounted on 1 in² copper pad of FR4 board; 270°C/W when mounted on min, copper pad.





SOT-23 Outline Dimension



SOT-23		
Dim	Min	Max
A	0.35	0.51
B	1.19	1.40
C	2.10	3.00
D	0.85	1.05
E	0.46	1.00
G	1.70	2.10
H	2.70	3.10
J	0.01	0.13
K	0.89	1.10
L	0.30	0.61
M	0.076	0.25